

UK Specifiers' Guide to Car Lifts with Driver on Board

There are two types of car lift supplied by Wöhr: 'Platform' and 'Platform with cover/lid'.

Please refer to [individual datasheets](#) for full details.

	Platform Lifts V07 and V08		Platform Lifts with Cover/Lid 'pop up' type MOB and MOB2	
	Usually for indoor installations, with a constructed enclosure at the entrance level.		Generally for outdoor installations in driveways or courtyards, where the cover/lid can be covered with materials to blend in with its surroundings.	
	Different weight capacities and platform lengths		Different weight capacities, lengths and travel distances	
Lift Model	V07 Lift (Standard weight and length)	V08 Lift (Increased weight and length)	MOB2 Lift (Standard weight and length, but high travel)	MOB Lift (Increased weight and length, but low travel)
Maximum weight capacity	2700kg	3200kg	2700kg	3500kg
Maximum travel distance	11.90m	11.90m	11.90m	5.0m
Maximum platform length	5.60m	6.50m	5.60m	6.50m
Maximum platform width	2.70m	2.80m	2.70m	2.80m

Please note the FF41/42 lifts mentioned in other parts of the web site were re-named in 2014 as MOB lifts.

Examples of Requirements and the Correct Lift to Choose

Example one

A lift is required to transport standard-sized cars to, for example, a basement garage area within a building. The lift is within the building. In this case you could choose the V07 open platform lift as the weight capacity will be sufficient for normal cars and 4x4s.

An example of the use of a V07 lift is [Tavern Lodge](#).

Example two

A lift is required as in example one above, but for very large cars such as Rolls Royce Phantom Extended wheelbase. In this case you could choose the V08 open platform lift as the larger weight capacity and length of platform will be suitable for these very large cars. An example site is Logan's Place London.

Example three

A lift for standard sized cars, with a lift travel distance greater than 5m, is required either inside a garage or outside in a driveway or courtyard. When closed/lowered the floor level is reinstated with the same surfacing materials, which means that the lift will be almost invisible. This lift can be driven over when not in use. In this case you could choose the MOB2 lift with cover lid such as the Horton Street, Kensington project.

Example four

As example three but the lift has to be able to take very large cars such as Roll Royce Phantom Extended wheelbase. And has a maximum travel distance of 5m or less. You could choose the MOB lift such as used with the project [Falcon House](#).